

PR* - PERISTALTIC DOSING PUMPS

Peristaltic dosing pumps suitable for dosing detergents. Polypropylene container, Santoprene membrane tubes with coupling. IP65 protection.

Comply with the provisions contained in the following international standards:

- 73/23CEE of 19/2/73
- 89/336CEE of 3/5/89
- EN60335-1



Fixed speed peristaltic pump

Power supply 230V. Power consumption 3,5W

	l/h	bar
PE1	1.5	0.1
PE3	3	0.1

Peristaltic pump with analogic speed adjustment

Power supply 230V. Power consumption 3,5W

	l/h	bar
PR4	0.6...4	0.1
PR7	1.2...7	0.1

Fixed speed peristaltic pump with analogic adjustment of dosing time

Models powered via single or double solenoid valves available. Two setting trimmers enable detergent Initial Charge and Make Up Charge. Power supply: 230 Vac. Power consumption: 3.5 W

Initial Charge time 18 to 180 sec. - Make Up Charge time 2 to 15 sec.

	l/h	bar
PRT6	6	0.1
PRT9	9	0.1



SATEMA

13856 VIGLIANO B.SE - Via Milano, 395

Tel. +39 015811102 - Fax 0158853029

Mail: info@satema.it <http://www.satema.it>