

18ACCA-POL98SH 98 SHORE POLYURETHANE TUBE

Extruded polyurethane tubes, Shore 98 polyester base for industrial pneumatic applications.



Diameter			@ 23 °C		
external	internal	thickness	Working pressure P1 bar	Burst pressure P2 bar	Bending radius mm
4	2,5	0,75	15	46	10
5	3	1	17	50	10
6	4	1	13	40	20
8	6	1	10	29	25
10	8	1	7	22	35

Tolerances on the external diameter

From 4 mm to 8 mm : +/- 0,10 mm

From 10 mm to 12 mm : +/- 0,15 mm

Working Temperature: from -40° C to +60°C

Pressure variations as a function of temperature

T (°C)	20	30	40	50	60
Pressure %	100	83	72	64	47

Code	Description
18ACCA-POL98SH-4X2,5	ELASTOFLES LIGHT BLUE TUBE 4X2,5 98 sh
18ACCA-POL98SH-5X3	ELASTOFLEX BLUE TUBE 5X3 98sh
18ACCA-POL98SH-6X4	ELASTOFLES LIGHT BLUE TUBE 6X4 98sh
18ACCA-POL98SH-8X6	ELASTOFLES LIGHT BLUE TUBE 8X6 98sh
18ACCA-POL98SH-10X8	ELASTOFLES LIGHT BLUE TUBE 10X8 98sh



SATEMA

13856 VIGLIANO B.SE - Via Milano, 395

Tel. +39 015811102

Mail: info@satema.it

<http://www.satema.it>

18_049